Waterless Wok Burners





Ģ

- Features:
- IAPMO GasMark Certified
- Front gutter design.
- 14" cast iron wok ring.
- Even high heat output.
- Height adjustable feet.
- Stainless steel exterior.
- Removable spillage tray.

• Condiment shelf on splash back.

1800

WĢ

WWĢ

- Modern design ideal for all day boiling.
- Flame failure & pilot standard with all models.

Ģ

WWG

D

• Extra high splash back with swivel laundry arm.

Specification

- Powerful duckbill or chimney jet burner. (Combination burner available on request, additional fee applies).
- Flat front panel for valve control by hand turn or knee push.

2800

SPICE TRA

Ģ

WWG

D

845

Chimney Burner

Duckbill Burner

opoonioution				
Model	(All 14" Wok Ring)	Natural Gas	LP Gas	Dimensions (W x D x H)
LKK-2B	(Duckbill Burner)	270 ^{MJ/h}	$202^{MJ/h}$	1200mm x 845mm x 740mm (working height)
LKK-2BC	(Chimney Burner) 🥥) 222 ^{MJ/h}	200 ^{MJ/h}	1200mm x 845mm x 740mm (working height)
LKK-3B	(Duckbill Burner) 👹	405 ^{MJ/h}	303 ^{MJ/h}	1800mm x 845mm x 740mm (working height)
LKK-3BC	(Chimney Burner) 🥥	333 ^{MJ/h}	300 ^{MJ/h}	1800mm x 845mm x 740mm (working height)
LKK-4B	(Duckbill Burner)	540 ^{MJ/h}	404 ^{MJ/h}	2800mm x 845mm x 740mm (working height)
LKK-4BC	(Chimney Burner) 🥥	444 ^{MJ/h}	$400^{\text{MJ/h}}$	2800mm x 845mm x 740mm (working height)
* 165 ^{MJ/h} Available on request for Duckbill NG only. Additional fee applies				Height including splashback is 1260mm

Accessories: Gutter Strainer & Water bucket with water slide **Inlet:** Gas: ³/₄" BSP Water: ¹/₂" Compression

• Specifications and design are subject to change without notice • Pictures are for illustrative purposes only • 2015 July

sales@lkk.com.au

Waste Outlet: Drain: 2" BSP



 New Zealand
 Phone: (+64) 09 837 2960 Fax: (+64) 09 836 9168

 (Head Office)
 18 Paramount Drive, Henderson, Auckland

 www.lkk.co.nz
 sales@lkk.co.nz

 Australia
 Phone: 1300 655 715
 Fax: (+61) 02 8587 0033

 47 George St, Clyde Sydney, NSW 2142, Sydney
 Sydney

www.lkk.com.au

Authorised Retailer: